



SPRING



6400 4 / 5 m



6410 3 / 4 / 5 m



6430 3 / 4 / 5 m



6440 3 / 4 / 5 m



6450 3 / 4 / 5 m



6470 3 / 4 / 5 m



6480 4 / 5 m



6490 3 / 4 / 5 m

SPRING



textilní podlahová krytina s všívaným smyčkovým vlasem scroll
na filcovém podkladu z polyesteru

Užitná třída
22
EN 1307



Výška celkem
9 mm
ISO 1765

Výška vlasu
7 mm
ISO 1766

Šíře role
3 / 4 / 5 m
EN 994



Váha celkem
1210 g/m²
ISO 8543



Váha vlasu
375 g/m²
ISO 2424

Stálobarevnost
≥ 5 - 6
ISO 105-B02



Voděodolnost
≥ 4 - 5
EN 1307



Materiál vlákna
100% PA
ISO 2424

Hustota všívání
ca 189 000 vpichů/m²
ISO 1763

Stupeň komfortu
LC 1
EN 1307



Skluznost povrchu
DS
EN 14041



Klasifikace hořlavosti
E_{fl}
EN 13501-1



Vhodné pro podlahové vytápění



Útlum kročejového hluku



Doporučená metoda instalace
Celoplošné lepení



Dovozce KARSIS s.r.o.